

Attachment Illustrated Parts List



MASSEY FERGUSON
LAWN & GARDEN EQUIPMENT

AGCO ALLIS

Simplicity
MANUFACTURING, INC.

500 N Spring Street / PO Box 997
Port Washington, WI 53074-0997 USA

© Copyright 2001 Simplicity Manufacturing, Inc. All Rights Reserved.

Rev. 4/2001


TP-400-2508-00-AT-SMA

38" Turbo Mounting Kit

985841

NOTE: Unless noted otherwise,
use the standard hardware torque
specification chart.

Kit Parts Included



The above parts group applies to the following Mfg. Nos.:

1693978 38" Turbo Mounting Kit

38" Turbo Mounting Kit

REF NO.	PART NO.	QTY.	DESCRIPTION
1	1705141	1	V-BELT
2	1704983	1	MOUNTING BRACKET
3	1960520	1	PAL NUT, 5/8
4	1931333	2	CARRIAGE BOLT, 5/16-18 x 3/4
5	1722546	1	PIVOT ASSY.
6	1931277	2	NUT, Hex, Flange, Whizlock, 5/16-18
7	1960404	4	SCREW, Truss Hd., #10-24 x 3/4
8	1933896	4	NUT, Nylock, #10-24
9	1718295	1	ROD, Deflector
10	1704789	1	BELT GUIDE, Turbo
11	1917372	4	NUT, Hex, 5/16-18
12	1917356	4	LOCKWASHER, 5/16
13	1921971	1	CAPSCREW, 3/8-16 x 1-1/4
14	1924940	2	WASHER, Flat, 3/8
15	1714817	1	IDLER PULLEY, 2-3/4" OD
16	1704768	1	BRACKET, Idler
17	172845	1	BELT STOP
18	1916965	1	LOCKWASHER, 3/8
19	1916950	1	NUT, Hex, 3/8-16
20	1713621	1	SPACER, Short, Splined
21	1713091	1	PULLEY ASSY., 4" OD
22	1713624	1	SPACER, Long
23	1679163	1	NUT, Wing Assy, 5/16
24	1923362	1	NUT, Hex, Center Lock, 5/16-18
25	1924856	2	SCREW, Taptite, 5/16-18 x 1/2
26	1704799	1	BRACE,
27	1705064	1	SPRING LATCH
28	1919381	1	WASHER, Flat
29	1960318	1	CAPSCREW, Hex Hd, 5/16-18 x 2-1/2
30	1960223	1	CARRIAGE BOLT, 5/16-18 x 1-1/4
31	1704881	1	BRACKET ASSY.,
32	1666294	1	SPACER
33	1705308	1	BRACKET, "L"
34	1930600	2	SCREW, Taptite, 5/16-18 x 1-1/2
35	1713540	1	ROLLER

Footnotes:

The above parts group applies to the following Mfg. Nos.:

1693978 38" Turbo Mounting Kit

Hardware Identification & Torque Specifications

Common Hardware Types

Hex Head Capscrew



Washer



Lockwasher

Carriage Bolt




Hex Nut

Standard Hardware Sizing

When a washer or nut is identified as **1/2"**, this is the *Nominal size*, meaning the *inside diameter* is 1/2 inch; if a second number is present it represent the *threads per inch*

When bolt or capscrew is identified as **1/2 - 16 x 2"**, this means the *Nominal size*, or *body diameter* is 1/2 inch; the second number represents the *threads per inch* (16 in this example, and the final number is the *body length* of the bolt or screw (in this example 2 inches long).

The guides and ruler furnished below are designed to help you select the appropriate hardware and tools.



Torque Specification Chart

FOR STANDARD MACHINE HARDWARE (Tolerance $\pm 20\%$)

Hardware Grade	No Marks SAE Grade 2		SAE Grade 5		SAE Grade 8	
	in/lbs ft/lbs	Nm.	in/lbs ft/lbs	Nm.	in/lbs ft/lbs	Nm.
8-32	19	2.1	30	3.4	41	4.6
8-36	20	2.3	31	3.5	43	4.9
10-24	27	3.1	43	4.9	60	6.8
10-32	31	3.5	49	5.5	68	7.7
1/4-20	66	7.6	8	10.9	12	16.3
1/4-28	76	8.6	10	13.6	14	19.0
5/16-18	11	15.0	17	23.1	25	34.0
5/16-24	12	16.3	19	25.8	27	34.0
3/8-16	20	27.2	30	40.8	45	61.2
3/8-24	23	31.3	35	47.6	50	68.0
7/16-14	30	40.8	50	68.0	70	95.2
7/16-20	35	47.6	55	74.8	80	108.8
1/2-13	50	68.0	75	102.0	110	149.6
1/2-20	55	74.8	90	122.4	120	163.2
9/16-12	65	88.4	110	149.6	150	204.0
9/16-18	75	102.0	120	163.2	170	231.2
5/8-11	90	122.4	150	204.0	220	299.2
5/8-18	100	136	180	244.8	240	326.4
3/4-10	160	217.6	260	353.6	386	525.0
3/4-16	180	244.8	300	408.0	420	571.2
7/8-9	140	190.4	400	544.0	600	816.0
7/8-14	155	210.8	440	598.4	660	897.6
1-8	220	299.2	580	788.8	900	1,244.0
1-12	240	326.4	640	870.4	1,000	1,360.0


NOTES

- These torque values are to be used for all hardware excluding: locknuts, self-tapping screws, thread forming screws, sheet metal screws and socket head setscrews.
- Recommended seating torque values for locknuts:
 - for prevailing torque locknuts - use 65% of grade 5 torques.
 - for flange whizlock nuts and screws - use 135% of grade 5 torques.
- Unless otherwise noted on assembly drawings, all torque values must meet this specification.


Wrench & Fastener Size Guide




1/4" Bolt or Nut
Wrench—7/16"




5/16" Bolt or Nut
Wrench—1/2"



3/8" Bolt or Nut
Wrench—9/16"



7/16" Bolt or Nut
Wrench (Bolt)—5/8"
Wrench (Nut)—11/16"



1/2" Bolt or Nut
Wrench—3/4"